



A LEADER IN CCTV SOLUTIONS, Surveillance, Security Camera, Security System, DVRs.

www.zmodo.net



DVR Catalog

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net



Content

DVR-M2104U 4 Channel Surveillance Security DVR	- 2 -
DVR-H9004U 4 Channel H.264 Real Time Security DVR	- 2 -
DVR-H9004V 4 Channel H.264 Real Time DVR w/ VGA	- 2 -
DVR-H9004UV 4 Channel H.264 Real Time Security DVR.....	- 2 -
DVR-H9004UT 4 Channel H.264 Real Time DVR w/ 7" LCD	- 2 -
DVR-H9004UVD 4 CH H.264 Real Time DVR w/ DVD Writer.....	- 2 -
DVR-H9008UV 8 CH H.264 Real Time Security DVR	- 2 -
DVR-H9008UVD 8 CH H.264 Real Time DVR w/ DVD Writer.....	- 2 -
DVR-H9006UVD 16 CH H.264 Real Time DVR w/ DVD Writer.....	- 2 -

DVR-M2104U 4 Channel Surveillance Security DVR



Product Overview

- Embedded Linux OS
- High Quality MPEG4 Video Compression
- Support SATA Hard Drive Up to 750GB
- Signal: NTSC /PAL
- Video Input / Output: BNC 4 / BNC 1
- Audio Input / Output: RCA 1 / RCA 1
- Display/Record Rate: 120 fps / 60fps
- Recording Mode: Continuous/Scheduled/Motion
- Display Mode: Each/Quad/Auto Switch/Hidden
- Network: RJ45 TCP/IP or DDNS
- Remote Access: LAN or IE Browser
- IR Remote Control
- Plug-n-Play

S

Model	DVR-M2104U - Standalone DVR
Video Compression	MPEG4
Video System	NTSC / PAL
Operation System	Linux Based
Video Input / Output	BNC 4-channe/1-Channel
Audio Input / Output	RCA 1-Channel / 1-Channel
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Display Resolution	NTSC: 720x480 / PAL: 720x576
Recording Resolution	NTSC: 720x220 / PAL: 720x288
Recording Frame Rate	NTSC: 60 fps / PAL: 50fps
Record Mode	Continuous/Motion detection/Time schedule
Playback Search	Time & Date, Event List
Display Mode	Each, Quad, Auto-switch
Remote Control	IR Remote Control
Simplex/Duplex/Triplex	Simplex
USB	For PC Playback & Backup / USB2.0
Network	RJ45, TCP/IP, DDNS, IE Based Controlled DVR
HDD Interface	SATA, Support up to 750GB
Power Supply	DC12V, 3A
Dimension	250 mm(D) x 235 mm(W) x 38 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net

DVR-H9004U 4 Channel H.264 Real Time Security DVR



Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 4 / BNC 2
- Audio Input / Output: RCA 1 / RCA 1
- Display/Record Rate: 120 fps / 120fps
- Network: TCP/IP, PPPoE, DHCP and DDNS
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- PTZ via RS-485 Port
- IR Remote Control
- Plug-n-Play

Model	DVR-H9004U - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 4-channel Input/2-Channel Output
Audio Input / Output	RCA 1-channel Input /1-Channel Output
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Display Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Recording Frame Rate	NTSC: 120 fps / PAL: 100 fps
Record Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Simplex / Duplex /Triplex / Pentaplex	Pentaplex
Network	TCP/IP, PPPoE, DHCP and DDNS
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
HDD Interface	SATA, Support up to 1TB
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Normal Play, Fast Forward, Fast Rewind, Frame by Frame
USB	USB Backup/USB 2.0
Remote Control	IR Remote Control
Power Supply	DC12V, 3A
Dimension	300 mm(W) x 220 mm(D) x 47 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net

DVR-H9004V 4 Channel H.264 Real Time DVR w/ VGA



Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 4 / BNC 2
- Audio Input / Output: RCA 1 / RCA 1
- Other Video Output: VGA
- Display/Record Rate: 120 fps / 120fps
- Network: TCP/IP, PPPoE, DHCP and DDNS
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- PTZ via RS-485 Port
- IR Remote Control

Model	DVR-H9004V - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 4-channe Input/2-Channel Output
Audio Input / Output	RCA 1-channel Input /1-Channel Output
Other Video Output	VGA
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Display Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Recording Frame Rate	NTSC: 120 fps / PAL: 100 fps
Record Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Simplex / Duplex /Triplex / Pentaplex	Pentaplex
Network	TCP/IP, PPPoE, DHCP and DDNS
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
HDD Interface	SATA, Support up to 1TB
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Normal Play, Fast Forward, Fast Rewind, Frame by Frame
USB	USB Backup/USB 2.0
Remote Control	IR Remote Control
Power Supply	DC12V, 3A
Dimension	300 mm(W) x 220 mm(D) x 47 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net

DVR-H9004UV 4 Channel H.264 Real Time Security DVR

Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 4 / BNC 2
- Audio Input / Output: RCA 4 / RCA 2
- Other Video Output: VGA
- Display/Record Rate: 120 fps / 120fps
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- PTZ via RS-485 Port
- Sensor/Alarm: 4CH/ 1CH
- IR Remote Control

Model	DVR-H9004UV - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 4-channel Input/2-Channel Output
Audio Input / Output	RCA 4-channel Input /2-Channel Output
Other Video Output	VGA
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Display Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Recording Frame Rate	NTSC: 120 fps / PAL: 100 fps
Record Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Simplex / Duplex /Triplex / Pentaplex	Pentaplex
Network	TCP/IP, PPPoE, DHCP and DDNS
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
Sensor/Alarm	4CH/1CH
HDD Interface	SATA, Support up to 1TB
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Normal Play, Fast Forward, Fast Rewind, Frame by Frame
USB	USB Backup/USB 2.0
Power Supply	DC12V, 3A
Dimension	300 mm(W) x 220 mm(D) x 47 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net

DVR-H9004UT 4 Channel H.264 Real Time DVR w/ 7" LCD

Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Built-in Foldable 7" LCD Monitor!
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 4 / BNC 1
- Audio Input / Output: RCA 4 / RCA 2
- Display/Record Rate: 120 fps / 120fps
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- PTZ via RS-485 Port
- Sensor/Alarm: 4CH/ 1CH
- IR Remote Control

Model	DVR-H9004UT - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 4-channel Input/1-Channel Output
Audio Input / Output	RCA 4-channel Input /2-Channel Output
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Display Resolution	NTSC: CIF (352 x 240) / PAL: CIF (352 x 288)
Recording Frame Rate	NTSC: 120 fps / PAL: 100 fps
Simplex / Duplex /Triplex / Pentaplex	Pentaplex
Network	RJ45, 10M/100M
Net Protocol	TCP/IP, DDNS,UDP,DHCP,PPPoE
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
Monitor	Built-in Foldable 7" LCD Monitor
Sensor/Alarm	4CH/1CH
HDD Interface	SATA, Support up to 1TB
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Normal Play, Fast Forward, Fast Rewind, Frame by Frame
USB	USB Backup/USB 2.0
Power Supply	DC12V, 5A
Dimension	400 mm(W) x 288 mm(D) x 73 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929
Tech Support: Support@zmodo.net

DVR-H9004UVD 4 CH H.264 Real Time DVR w/ DVD Writer



Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Support DVD Writer for Back Up
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 4 / BNC 2
- Audio Input / Output: RCA 4 / RCA 2
- Other Video Output: VGA
- Display/Record Rate: 120 fps / 120fps
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- Sensor/Alarm/PTZ Control
- IR Remote Control

Model	DVR-H9004UVD - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 4-channel Input/2-Channel Output
Audio Input / Output	RCA 4-channel Input /2-Channel Output
Other Video Output	VGA
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Display Resolution	D1: 704 x 480 (NTSC) / 704 x 576 (PAL)
Recording Frame Rate	NTSC: 120 fps / PAL: 100 fps
Record Resolution	NTSC: CIF (352x240), HD1 (704x240), D1 (704x480) PAL: CIF (352x288), HD1 (704x288), D1 (704x576)
Net Protocol	TCP/IP, DDNS,UDP,DHCP,PPPoE
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
Sensor/Alarm	4CH/1CH
HDD Interface	SATA, Support up to 1TB
DVD-RW	DVD-RW for Backup
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Play / Slow / FWD / Frame by Frame
USB	USB Backup/USB 2.0
Power Supply	DC12V, 3A
Dimension	400 mm(W) x 288 mm(D) x 73 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net

DVR-H9008UV 8 CH H.264 Real Time Security DVR

Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 8 / BNC 2
- Audio Input / Output: RCA 1 / RCA 1
- Other Video Output: VGA
- Display/Record Rate: 240 fps / 240fps
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- PTZ via RS-485 Port
- Sensor/Alarm: 4CH/ 1CH
- IR Remote Control

Model	DVR-H9008UV - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 8-channel Input/2-Channel Output
Audio Input / Output	RCA 1-channel Input /1-Channel Output
Other Video Output	VGA
Display Frame Rate	NTSC: 240 fps / PAL: 200 fps
Display Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Recording Frame Rate	NTSC: 240 fps @CIF / PAL: 200 fps @CIF
Record Resolution	NTSC: 352 x 240 / PAL: 352 x 288
Simplex / Duplex/Triplex / Pentaplex	Pentaplex
Network	TCP/IP, PPPoE, DHCP and DDNS
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
Sensor/Alarm	8CH/1CH
HDD Interface	SATA, Support up to 1TB
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Normal Play, Fast Forward, Fast Rewind, Frame by Frame
USB	USB Backup/USB 2.0
Power Supply	DC12V, 3A
Dimension	300 mm(W) x 220 mm(D) x 47 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net

DVR-H9008UVD 8 CH H.264 Real Time DVR w/ DVD Writer



Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Support DVD Writer for Back Up
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 8 / BNC 2
- Audio Input / Output: RCA 1 / RCA 1
- Other Video Output: VGA
- Display/Record Rate: 240 fps / 240 fps
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- Sensor/Alarm/PTZ Control
- IR Remote Control

Model	DVR-H9008UVD - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 8-channel Input/2-Channel Output
Audio Input / Output	RCA 1-channel Input /1-Channel Output
Other Video Output	VGA
Display Frame Rate	NTSC: 240 fps / PAL: 200 fps
Display Resolution	D1: 720 x 480 (NTSC) / 720 x 576 (PAL)
Recording Frame Rate	NTSC: 240 fps @CIF / PAL: 200 fps @CIF
Record Resolution	NTSC: CIF (352x240), PAL: CIF (352x288)
Net Protocol	TCP/IP, DDNS,UDP,DHCP,PPPoE
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
Sensor/Alarm	8CH/1CH
HDD Interface	SATA, Support up to 1TB
DVD-RW	DVD-RW for Backup
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Play / Slow / FWD / Frame by Frame
USB	USB Backup/USB 2.0
Power Supply	DC12V, 3A
Dimension	400 mm(W) x 288 mm(D) x 73 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929

Tech Support: Support@zmodo.net

DVR-H9006UVD 16 CH H.264 Real Time DVR w/ DVD Writer

Product Overview

- Embedded Linux OS
- H.264 Video Compression
- Support DVD Writer for Back Up
- Support SATA Hard Drive Up to 1TB
- Signal: NTSC /PAL
- Video Input / Output: BNC 16 / BNC 2
- Audio Input / Output: RCA 4 / RCA 2
- Other Video Output: VGA
- Display/Record Rate: 480 fps / 480 fps
- Remote Access: LAN or IE Browser
- Support Live! Preview via 3G Mobile
- Sensor/Alarm/PTZ Control
- IR Remote Control

Model	DVR-H9006UVD - StandAlone DVR
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	BNC 16-channe Input/2-Channel Output
Audio Input / Output	RCA 4-channel Input /2-Channel Output
Other Video Output	VGA
Display Frame Rate	NTSC: 480 fps / PAL: 400 fps
Display Resolution	D1: 720 x 480 (NTSC) / 720 x 576 (PAL)
Recording Frame Rate	NTSC: 480 fps @CIF / PAL: 400 fps @CIF
Playback Resolution	NTSC: CIF (352x240)/ PAL: CIF (352x288)
Net Protocol	TCP/IP, DDNS,UDP,DHCP,PPPoE
Remote Access	LAN or Internet Browsing
PTZ Control	RS-485
Sensor/Alarm	16CH/1CH
HDD Interface	SATA, Support up to 1TB
DVD-RW	DVD-RW for Backup
Network Function	Support to Live View with IE & with Mobile Phone
Playback Mode	Play / Slow / FWD / Frame by Frame
USB	USB Backup/USB 2.0
Power Supply	DC12V, 5A
Dimension	430 mm(W) x 385 mm(D) x 65 mm(H)

Address: 1401 Interstate Dr., Champaign, IL 61822 Tel: 1 - 217 - 903- 5674 Fax: 1 - 217 - 351 - 2929
Tech Support: Support@zmodo.net